

Eurol Transfluid ATF-CVT

Fully synthetic multifunctional transmission oil for both automatic and continuously variable transmissions

Article number E113668 Version 1.5

Product information

Eurol Transfluid ATF-CVT is a fully synthetic multifunctional oil suitable for both automatic transmissions and continuously variable transmissions for vehicles produced in North and South America, Europe, and Asia.

Eurol Transfluid ATF-CVT ensures that automatic and continuously variable transmissions continue to shift smoothly under heavy conditions, as the product prevents unnecessary friction. The low pour point and high VI ensure that Eurol Transfluid ATF-CVT can be used across a wide temperature range.

The combination of high-quality base oils with a state-of-the-art additive that can be used for both ATF and CVT applications results in a very extensive list of applications where Eurol Transfluid ATF-CVT can be utilized.

Eurol Transfluid ATF-CVT retains its excellent properties and comfortably meets the prescribed service intervals due to its very good oxidation and thermal stability.

Because Eurol Transfluid ATF-CVT is suitable for both automatic and continuously variable transmissions, it has a very broad applicability and an extensive 'suitable for use' list with specifications for which it can be used.

Recommended for use

- Aisin Warner AW-1
- ATF RED 1K
- ATF-Z1. Honda
- **GM Dexron III**
- Honda/Kia/Mitsubishi SP-III
- Hyundai/KIA CVT-1
- JWS 3309/3314/3317
- JWS 3320 (CVT)
- MB 236.1 236.11
- MB 236.20
- Mercon SP
- Mercon V
- Mitsubishi SP-IV
- Nissan ePower
- Nissan Matic C, D, J, K, P, S
- Nissan NS-1
- Nissan NS-2
- Nissan NS-3
- Toyota CVT FE
- Volvo 97325
- Volvo 97335
- Voor meer specificaties, kijk op de website eurol.com
- VW G 052 055
- VW G 052 180
- VW G 052 516
- VW G 055 025
- ZF Lifequardfluid 5, 6, 8



Eurol Transfluid ATF-CVT

Fully synthetic multifunctional transmission oil for both automatic and continuously variable transmissions

Article number E113668 Version 1.5

Physical properties

Property/Test	Value/Result	ASTM Standard
Color	brown	
Density at 20°C	0.84 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	34.2 cSt	ASTM D 445
Viscosity, kinematic at 100°C	7.2 cSt	ASTM D 445
Viscosity Index	180	ASTM D 2270
Flash Point	213 °C	ASTM D 92
Pour point	-45 °C	ASTM D 97